




INSTALL INSTRUCTIONS

Satellite communicator

1 Device installation:

- 1.1 The device comes with a special bag to secure the device to a mast using velcro strips.
- 1.2 The device must be placed outdoor, away from transmission devices and in such a position as to ensure the maximum sky visibility.
- 1.3 The device antenna is on the side with the adhesive number and this side must be placed horizontally towards the sky. If not possible to install horizontally, install it vertically on a chandelier with the adhesive side towards the exterior of the vessel.
- 1.4 Finally secure the device using the safety rope string.

WARNING: If the antenna side is not installed towards sky position or if it's covered by other objects transmission may not work properly.





2 Device activation / deactivation:

- 2.1 The device must be activated only after it has been placed on board in outdoor position and behind the boat.
- 2.2 Safely unscrew the two fixing screws on the device cap, remove the cap and push the **ON** button and reposition the cap (see figure at right). Viceversa, to deactivate the device push the **OFF** button and replace the cap.

WARNING: Always activate the device outdoor, otherwise the device may freeze, malfunction and even be damaged. For the same reason always deactivate the device before taking it indoor and return it.

Button in OFF position
(Disactivated)



Button in ON position
(Activated)

3 What to do if the device is not transmitting after correct positioning?

- 3.1 Remove the activation cap.
- 3.2 Place the activation button to **OFF**, wait 1 minut and reposition to **ON**.
- 3.3 Check if position arrives in Livetrack application within 15 minutes.
If necessary repeat the deactivation/activation procedure again.



SGS TRACKING

Via Pedullà 59 - 16165 Genoa - Italy

P +39 010.8301222 | F +39 010.8301278 | info@sgstracking.com | www.sgstracking.com